



Powered By:



EASE OF TRANSPORT

SOLAR POWERED

DURABLE

COST EFFECTIVE



PRODUCT SPECIFICATIONS

GENERAL

Model	CCTV Tower - GP2CTP
Camera Quality	2x4MP acusense deep learning cameras, 50m night vision
Mast Height	4.5 Metres
Mast Type	Cable winch
Cameras	2 x Hikvision 99° field of view
Recording Time	4 weeks continuous recording
Monitoring (Live/ Playback)	Phone App or PC
Lifting	Fork Pockets & Lifting Lugs
Communications	4G Router Wi-Fi Hotspot (Optional)
Features	Flashing beacon, scheduled recordings, email/app alerts, optional speaker, false alarm reduction

OPERATIONAL DATA

Wind Rating	100km/h
Working Temperature	0°C to 50°C (-25°C with optional kit)

BATTERY

Battery	2.6kWh Lithium Ion (LFP)
Runtime	104 Hours
Solar	340Wp
Solar Tilt	0 to 90°
Solar Orientation	0 to 360°
Efficiency (solar)	1 hr of sun / 12 hrs recording

UNIT INFORMATION

Dimensions (Stowed)	1000 x 1000 x 2900 (LxWxH)
Dimensions (Deployed)	1650 x 1000 x 5850 (LxWxH)
Weight	800kg